




Shandong Chik Bearing Co., Ltd.



VA201



ZZ/VA201



ZZ/VA208



ZZ/VA228

65 mm x 120 mm x 23 mm SKF 6213/VA201 deep groove ball bearings

Bearing No. 6213/VA201

6213/VA201 Bearing 2D drawings and 3D CAD models

Size	65x120x23 mm
Bore Diameter	65 mm
Outer Diameter	120 mm
Width	23 mm
d	65 mm
D	120 mm
B	23 mm
C	23 mm
d1	83,3 mm
r1 min.	1,5 mm
r2 min.	1,5 mm
D2	106 mm
Weight	1 Kg
Temperature -	30 to +250 °
Basic static load rating (C0)	40,5 kN
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.008
EAN	7316571026961
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No



Shandong Chik Bearing Co., Ltd.

Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Features; C0-
Other Features	Deep Groove Extreme Temperature Variant
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6213/VA201
Weight / LBS	1
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Bore	2.559 Inch 65 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
bore diameter:	65 mm
static load capacity:	40.5 kN
outside diameter:	120 mm
precision rating:	Not Rated
overall width:	23 mm



Shandong Chik Bearing Co., Ltd.

finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	23 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1.5 mm
snap ring included:	Without Snap Ring
maximum rpm:	90 RPM
internal clearance:	C0
series:	62
operating temperature range:	-20 to +480 ° F
resistance features:	Corrosion Resistant, Extreme Temperature
d_1	83.3 mm
D_2	105.8 mm
$r_{1,2}$ min.	1.5 mm
d_a min.	74 mm
D_a max.	111 mm
r_a max.	1.5 mm
Basic dynamic load rating C	58.5 kN
Basic static load rating C_0	40.5 kN
Limiting speed	90 r/min
Limiting temperature T max.	250 ° C
Mass bearing	1.01 kg