



# Shandong Chik Bearing Co., Ltd.

## KOYO K60X65X20H needle roller bearings



K60X65X20H Bearing 2D drawings and 3D CAD models

Bearing No. K60X65X20H

Bore Diameter	60 mm
Outer Diameter	65 mm
Fw	60 mm
Ew	65 mm
Bc	20 mm
Weight	0.046 Kg
Basic dynamic load rating (C)	31.9 kN
Basic static load rating (C0)	78.1 kN
(Grease) Lubrication Speed	4500 r/min
(Oil) Lubrication Speed	6900 r/min
Category	Needle Non Thrust Roller Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.05
EAN	0060579019609
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	Not Applicable



## Shandong Chik Bearing Co., Ltd.

Inch - Metric	Metric
Thrust Bearing	No
Long Description	60MM Bore; 65MM Outside Diameter; 20MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Other Features	Radial Roller   Hardened Steel Cage
Category	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Manufacturer Item Number	K60X65X20H
Weight / LBS	0.101
Outside Diameter	2.559 Inch   65 Millimeter
Bore	2.362 Inch   60 Millimeter
Width	0.787 Inch   20 Millimeter
Bearing No.	K60X65X20H
Cr	31.9
C0r	78.1
Cu	12.2
Grease lub.	4500
Oil lub.	6900
P/S	S
(Refer.) Mass(kg)	0.046
Shaft(max.)	60.000
Shaft(min.)	59.987
Housing(max.)	65.029
Housing(min.)	65.010



# Shandong Chik Bearing Co., Ltd.